



LIGHTING LEGEND

- DEXTRA-AME8 M3 8W SELF CONTAINED POLYCARBONATE BULKHEAD
- DEXTRA-2D-AMES128/HF/WP
- DEXTRA-2D-AMES128/HF/M3/WP EMERGENCY VERSION
- IP56 PIR OPERATED 150W HALOGEN FLOODLIGHT
- CRABTREE 1G 1W LIGHT SWITCH-C/W BOX, GRID & FACEPLATE
- CRABTREE 1G 2W LIGHT SWITCH-C/W BOX, GRID & FACEPLATE
- CRABTREE KEY SWITCH OVERRIDE FOR PIR FAILURE C/W BOX,GRID & FACEPLATE
- CRABTREE ISOLATOR/EM LIGHT TEST SWITCH-C/W BOX, GRID & FACEPLATE
- STEINEL PIR DETECTOR I.S.3180 C/W PHOTOCELL (CONTROLLER)
- DEXTRA-LUXTS 149 EL AC-TWIN IP RATED FLUO FITTING
- DEXTRA-LUXTS 149 EL AC E3-TWIN IP RATED FLUO FITTING EMERGENCY VERSION
- DANLERS-CEFL PIR C/W PHOTOCELL
- DEXTRA-EX18 NM3 C/W EX10L-EXIT BOX LIGHT

ELECTRICAL LEGEND

- 2GANG 13A SWITCHED SOCKET OUTLET
- SWITCHED FUSED CONNECTION UNIT
- IP56 OUTLET WITH ISOLATOR FOR APPLIANCES
- ISOLATOR @ HIGH LEVEL
- ISOLATOR
- EXTRACT FAN LOCALLY CONTROLLED VIA SFS
- UNIT AT HIGH LEVEL
- UNIT AT LOW LEVEL
- NEW POWER DB, LIGHTING DB& HEAT/VENTILATION DB SEPERATELY METERED AS L2 REGULATION.
- INLINE INSTANTANEOUS HOT WATER HEATER
- NEW HVAC UNIT BY OTHERS - CONTRACTOR TO PROVIDE FUSED SPUR TO ALLOW FINAL CONNECTION BY OTHERS