



EE KEY

EE – denotes Part L compliancy (45 lumen efficacy)
ES – energy saving (40 lumen efficacy)

Ceiling recessed spotlights
8w 700mA Polespring B667901 – white EE

Semi recessed lights
20w 12v Mini Starlight A151307 – bright chrome

Semi recessed lights
1w 350mA LED Eyelid Under Cupboard Light – L507410 anodised aluminium ES
1w 350mA Lucca 30° (as downlight) E807728 – primed ES
7.68w/m 24v Contour L197400 – warm white EE
Heat sink tape for above – Y170110

Decorative lighting – supplied by client
Decorative table lamp

Sockets and control
5amp wall socket
Dimmer switch
Switch
Supply

Setting out on plan
Equal distance
Centre Line
Distance off
Ceiling height
In line with

BEAMWIDTHS

Bi Pin Capsule Lamp 12v
M47 – 20w
8w 700mA Warm White Static Dim
T611001 – 10°
T612001 – 20°

Lenses and Louvers
SG – sandblasted glass lens

PLANS MUST BE READ IN CONJUNCTION WITH SPECIFICATION

Notes:

1. All Polesprings to be installed in the direction as shown on plan and ceiling ring to be fully chamfered to allow for full tilt in all cases.
2. Where fittings are relevant to furniture and paintings, client to confirm to electrician exact locations.
3. Electrician to source locations for remote drivers prior to first fix.
4. Group remote drivers required for LED Polesprings and 0-10v wiring required.
5. All Contour measurements must be confirmed prior to order.

JOHN CULLEN

LIGHTING FOR HOUSE AND GARDEN

Client Name: Michelle Coulter

Client Code: COU032 Specification No: 21319

Site Address: 29 NASSAU ROAD, LONDON SW13 9QF

Drawing Title: Media room lighting plan

Scale: DO NOT SCALE

First Issue: 21.10.2011 Revision:

Designer: Zoe Duff Gordon – 020 73715400

Sales: Jack Kartrieber – 020 7371 9000

